



NOTES: nts

- ① "SUBSTRATE": *
TYPICAL NORMAL WEIGHT
CONCRETE
- ② FIRST PLY: (A7400)
"LAURENCO ROOFING -
WPFG SHEET" SET IN
FULL BED OF LAURENCO
LIQUID ADHESIVE (A7005)
- ③ SECOND PLY:
"LAURENCO ROOFING -
WPFG SHEET" (A7400),
SET IN FULL BED OF
LAURENCO LIQUID
ADHESIVE (A7005)
- ④ "SPC": STANDARD
PROTECTION SHEET-
SPC (A740) IN FULL
BED OF LAURENCO
LIQUID ADHESIVE
(A7005)
- ⑤ LAURENCO BUTYL TAPE
(A75002) (A75004)
SET IN LIGHT COATING
OF LAURENCO LIQUID
ADHESIVE (A7005)
- ⑥ ⑦ ⑧ N/A
- ⑨ FBC LAURENCO PMMA:
(83231) WITH UNIVERSAL
"BLUE" PRIMER (83237)
AND PMMA REINFT
FLEECE (83235)

NB: • MVS - A/B (A38003 +
A38101) TO BE APPLIED
TO "GREEN" CONCRETE
10 HOURS BEFORE ANY
PMMA PRODUCT

• OVERBURDEN BY
OTHERS

* NORMAL WEIGHT CONCRETE
IS PREFERRED. THE USE OF
LIGHTWEIGHT STRUCTURAL
CONCRETE REQUIRES USE
OF MVS A/B (A38003 + A38101)

 **LAURENCO WATERPROOFING™** ©
A DIVISION OF FBC CHEMICAL CORPORATION

COMP-001 DECK-TO-WALL W/ PMMA BASE FLASHING