



NOTES: nts

- ① "SUBSTRATE":
TYPICAL NORMAL WEIGHT
CONCRETE
- ② FIRST PLY: (A7400)
"LAURENCO ROOFING -
WPGF SHEET" SET IN
FULL BED OF LAURENCO
LIQUID ADHESIVE (A7005)
- ③ SECOND PLY:
"LAURENCO ROOFING -
WPGF SHEET" (A7400),
SET IN FULL BED OF
LAURENCO LIQUID
ADHESIVE (A7005)
- ④ "SPC": STANDARD
PROTECTION SHEET-
SPC (A740) IN FULL
BED OF LAURENCO
LIQUID ADHESIVE
(A7005)
- ⑤ LAURENCO BUTYL TAPE
(A75002) (A75004)
SET IN LIGHT COATING
OF LAURENCO LIQUID
ADHESIVE (A7005)

PMMA :

REINFORCED PMMA
FLASHING (83231) RESIN /
REINFORCING FLEECE
(83236) / PRIMER (83237)
NOT SHOWN FOR
CLARITY

* NORMAL WEIGHT CONCRETE
IS PREFERRED. THE USE OF
LIGHTWEIGHT STRUCTURAL
CONCRETE REQUIRES USE
OF MVS A/B (A38003 + A38101)

* SEALANT AND BACKER ROD
BY OTHERS

LAURENCO WATERPROOFING™ ©
A DIVISION OF FBC CHEMICAL CORPORATION

COMP - 002 COMPOSITE FLASHING AT PIPE PENETRATION - PMMA TO RMA DECK