


NOTES: nts

- ① "SUBSTRATE":  
TYPICAL NORMAL WEIGHT  
CONCRETE
- ② FIRST PLY: (A7400)  
"LAURENCO ROOFING -  
WPFG SHEET" SET IN  
FULL BED OF LAURENCO  
LIQUID ADHESIVE (A7005)
- ③ SECOND PLY:  
"LAURENCO ROOFING -  
WPFG SHEET" (A7400),  
SET IN FULL BED OF  
LAURENCO LIQUID  
ADHESIVE (A7005)
- ④ "SPC": STANDARD  
PROTECTION SHEET-  
SPC (A740) IN FULL  
BED OF LAURENCO  
LIQUID ADHESIVE  
(A7005)
- ⑤ LAURENCO BUTYL TAPE  
(A75002) (A75004)  
SET IN LIGHT COATING  
OF LAURENCO LIQUID  
ADHESIVE (A7005)
- \* A: SEALANT AND BACKER  
ROD AT ANNULAR SPACE  
BY OTHERS
- B: PIPE PENETRATION  
W/ SURFACE PREP,  
CLEANED, DRY, AND  
PRIMED
- ⑨ FBC LAURENCO PMMA:  
(83231) WITH UNIVERSAL  
"BLUE" PRIMER (83237)  
AND PMMA REINF'T  
FLEECE (83235)

NB: ⑥ ⑦ ⑧ N/A

\* NORMAL WEIGHT CONCRETE  
IS PREFERRED. THE USE OF  
LIGHTWEIGHT STRUCTURAL  
CONCRETE REQUIRES USE  
OF MVS A/B (A38003 + A38101)

\* ROUGH OPENING INFILL BY  
OTHERS (BACKER ROD AND  
SEALANT, NON-SHRINK  
GROUT FILL, MECHANICAL  
EXPANDING LINK SEAL, ETC.  
BY OTHERS)

 **LAURENCO WATERPROOFING™** ©  
A DIVISION OF FBC CHEMICAL CORPORATION

# COMP-004 PIPE PENETRATION VERTICAL