



NOTES: nts

- ① "SUBSTRATE":  
TYPICAL NORMAL WEIGHT  
CONCRETE
- ② SUBSTRATE W/ UNIVERSAL  
"BLUE PRIMER" (83237)
- ③ PMMA "H" RESIN (83240)  
OR PMMA FLASHING  
RESIN (83241) MIN. 45  
WET MILS.
- ④ REINFORCEMENT FLEECE  
(83236) ENCAPSULATED  
BETWEEN 2 WET LAYERS  
OF PMMA RESIN. @ 45  
WET MILS.
- ⑤ LAURENCO BUTYL TAPE  
(A75002, A75004)  
SET IN LIGHT COATING  
OF LAURENCO LIQUID  
ADHESIVE (A7005)

\* 1/4" EXTEND LIQUID RESIN 1/4"  
MIN. BEYOND FLEECE  
REINFT

\* NORMAL WEIGHT CONCRETE  
IS PREFERRED. THE USE OF  
LIGHTWEIGHT STRUCTURAL  
CONCRETE REQUIRES USE  
OF MVS A/B (A38003 + A38101)

\*\* OVERBURDEN BY OTHERS.  
NOT SHOWN FOR CLARITY

**LAURENCO WATERPROOFING™** ©  
A DIVISION OF FBC CHEMICAL CORPORATION

**PMMA-003 TYPICAL PMMA BASE FLASHING**