



NOTES: nts

- ① "SUBSTRATE":
TYPICAL NORMAL * WEIGHT
CONCRETE
- ② FIRST PLY: (A7400)
"LAURENCO ROOFING -
WPFG SHEET" SET IN
FULL BED OF LAURENCO
LIQUID ADHESIVE (A7005)
- ③ SECOND PLY:
"LAURENCO ROOFING -
WPFG SHEET" (A7400),
SET IN FULL BED OF
LAURENCO LIQUID
ADHESIVE (A7005)
- ④ "SPC": STANDARD
PROTECTION SHEET-
SPC (A740) IN FULL
BED OF LAURENCO
LIQUID ADHESIVE
(A7005)
- ⑤ LAURENCO BUTYL TAPE
(A75002) (A75004)
SET IN LIGHT COATING
OF LAURENCO LIQUID
ADHESIVE (A7005)
- ⑥ STAINLESS STEEL (SS)
TERMINATION BAR
MECHANICALLY
FASTENED W/ SS
FASTENERS
- ⑦ - TOP EDGE DETAILED
WITH LAURENCO
RUBBERIZED
FLASHING COATING
(A7305)

* NORMAL WEIGHT CONCRETE
IS PREFERRED. THE USE OF
LIGHTWEIGHT STRUCTURAL
CONCRETE REQUIRES USE
OF MVS A/B (A38003 + A38101)

LAURENCO WATERPROOFING™ ©
A DIVISION OF FBC CHEMICAL CORPORATION

RMA - 003 TYPICAL DECK-TO-WALL TRANSITION