



NOTES: nts

- ① "SUBSTRATE":  
TYPICAL NORMAL WEIGHT  
CONCRETE
- ② FIRST PLY: (A7400)  
"LAURENCO ROOFING -  
WPFG SHEET" SET IN  
FULL BED OF LAURENCO  
LIQUID ADHESIVE (A7005)
- ③ SECOND PLY:  
"LAURENCO ROOFING -  
WPFG SHEET" (A7400),  
SET IN FULL BED OF  
LAURENCO LIQUID  
ADHESIVE (A7005)
- ④ "SPC": STANDARD  
PROTECTION SHEET-  
SPC (A740) IN FULL  
BED OF LAURENCO  
LIQUID ADHESIVE  
(A7005)
- ⑤ LAURENCO BUTYL TAPE  
(A75002) (A75004)  
SET IN LIGHT COATING  
OF LAURENCO LIQUID  
ADHESIVE (A7005)
- ⑥A STAINLESS STEEL BAND  
W/ BUTYL TAPE AND  
TROWEL GRADE DETAIL
- ⑦ TOP EDGE DETAILED  
WITH LAURENCO  
RUBBERIZED FLASHING  
COATING (A7305)

note: PLIES

- A. FINGER FLASHING 4"
- B. FINGER FLASHING 5"
- C. TARGET PATCH - 1
- D. TARGET PATCH - 2
- E. FIELD PLY TIE-IN
- F. Ⓞ SPC PROTECTION

\* NORMAL WEIGHT CONCRETE  
IS PREFERRED. THE USE OF  
LIGHTWEIGHT STRUCTURAL  
CONCRETE REQUIRES USE  
OF MVS A/B (A38003 + A38101)