



NOTES: nts

- ① "SUBSTRATE":
TYPICAL NORMAL WEIGHT
CONCRETE
- ② FIRST PLY: (A7400)
"LAURENCO ROOFING -
WPGF SHEET" SET IN
FULL BED OF LAURENCO
LIQUID ADHESIVE (A7005)
- ③ SECOND PLY:
"LAURENCO ROOFING -
WPGF SHEET" (A7400),
SET IN FULL BED OF
LAURENCO LIQUID
ADHESIVE (A7005)
- ④ "SPC": STANDARD
PROTECTION SHEET-
SPC (A740) IN FULL
BED OF LAURENCO
LIQUID ADHESIVE
(A7005)
- ⑤ BUTYL TAPE AT JOINT
BETWEEN DRAIN BODY
AND CONCRETE
SUBSTRATE
- ⑥ TARGET PATCH OF
1-PLY OF A7400 SHEET
IN LIQUID
- ⑦ DRAIN CLAMPING RING:
EXTEND TARGET
PATCH, FIRST, AND
SECOND PLY 1-INCH
MINIMUM BEYOND
CLAMPING RING

* NORMAL WEIGHT CONCRETE
IS PREFERRED. THE USE OF
LIGHTWEIGHT STRUCTURAL
CONCRETE REQUIRES USE
OF MVS A/B (A38003 + A38101)

LAURENCO WATERPROOFING™ ©
A DIVISION OF FBC CHEMICAL CORPORATION

RMA-007 ROOF DRAIN FLASHING